ART. 234

Pistoni otturatori con doppio anello per tubazioni in acciaio, ghisa e polietilene dal DN 2,1/2" al DN 12" per collaudi bassa e media pressione. Versione passante completa di valvola e manometro con protezione in gomma.
Sono costruiti con flange in alluminio anticorodal tornite.
Anelli in gomma naturale con spigoli arrotondati anti taglio (come per art. 001-002-003).
Maniglia in acciaio montata su cuscinetto reggi spinta.
Plugging pistons with double ring for steel, cast iron and polyethylene pipelines, from DN 2,1/2" to DN 12" for testing at low and middle pressure. Passing version with valve and manometer with rubber protection.
They are made with anticorodal aluminium turned flanges.
Natural rubber rings with rounded corners anti-cut (as for art. 001-002-003).
Steel handle assembled on step-bearing.

ART. 235

Come art. 234 ma con singolo anello.
Like art. 234, but with single ring.



ART. 236

Pistoni otturatori a singolo anello per tubazioni in acciaio, ghisa e polietilene dal DN 2,1/2" al DN 12" per collaudi bassa e media pressione.
Sono costruiti con flange in alluminio anticorodal tornite.
Anelli in gomma naturale con spigoli arrotondati anti taglio (come per art. 001-002- 003). Maniglia in acciaio montata su cuscinetto reggi spinta.
Pluggins pistons with single ring for steel, cast iron and polyethylene pipelines, from DN 2,1/2" to DN 12" for testing at low and middle pressure. They are made with anticorodal aluminium turned flanges.
Natural rubber rings with rounded corners anti-cut (as for art. 001-002-003).
Steel handle assembled on a step-bearing.

