ART. 242

Sfera di chiusura, DN 1", per staffa porta contatore, assemblata come da figura con puntalino di posizionamento.
Costruita interamente in acciaio, è dotata di **sede per chiave esagonale antislittamento.**
Closing sphere DN 1", for metre-holder flask, assembled as in the picture with positioning cap. Made entirely of steel, it is equipped with **a seat for an antiskid hexagonal wrench.**





ART. 243

Sfera dichiusura per piccoli diametri (da 1/2" a 2"), costruita in acciaio zincato, con asta montata su ralla reggi spinta da 350 mm e sfera in gomma naturale piena. E' dotata di **sede per chiave esagonale antislittamento.**
Closing sphere for small diameters (from 1/2" to 2"), made in zincplated steel, with the rod assembled on the trust-bearing fifth wheel of 350 mm and sphere in solid natural rubber.
It is equipped with **a seat for an antiskid hexagonal wrench.**



ART. 244

Sfera di chiusura per piccoli diametri (da 1" a 2"), costruita in acciaio zincato, con asta montata su ralla reggi spinta e sfera in gomma naturale piena. Versione passante con valvola e manometro con protezione in gomma, indicata per collaudi bassa e media pressione.
Closing sphere for small diameters (from 1" to 2"), made in zinc-plated steel, with the rod assembled on the thrust-bearing fifth wheel and sphere in solid natural rubber.
Passing version with valve and manometer with rubber protection, fit for tests at low and middle pressure.

