ART. 28

La macchina foratubi (ART. 28) è costruita in acciaio al carbonio con nichelatura chimica altamente resistente alla corrosione e permette di realizzare fori, in qualunque posizione, su reti gas e acqua a media e alta pressione da 1" a 6" fino a 50 BAR (Su richiesta, anche fino ad 80 BAR).
Corsa utile di 280 mm.
Cuscinetto a rulli montato sulla bussola porta raccordi che permette una foratura coassiale alla macchina in qualsiasi posizione. O-Ring di tenuta alla pressione, corpo macchina e cuscinetti protetti da corteco.
La macchina è dotata di albero centrale in acciaio al carbonio cromato, valvola di sfiato e doppio fine corsa di sicurezza.
La macchina viene fornita in cassetta metallica con gli stessi accessori del ART. 22.

The pipe drilling machine (ART. 28) is made of carbon steel with chemical nickel plating and it allows to make hole, in any position, on middle and high pressure gas and water pipe-lines from 1" to 6" up to 50 BAR (on request, up to 80 BAR).
Working stroke: 280 mm.
Roller bearing mounted on the connector-holder bush to make a coaxial drilling in any position.
O-ring, machine body and bearings are protected by a lip-seal inserted in the bush.
Carbon steel center shaft with chromium plating.
Air-valve placed on the machine and double safety limit switch.
The machine comes supplied in metallic box with the same accessories of ART. 22.





La cassetta contenente la macchina foratubi comprende i seguenti accessori necessari al suo montaggio/funzionamento.
The pipe-drilling machine is supplied in a metallic box with two hole saws, available in the following diameters.

n°	ACCESSORI	CARATTERISTICHE	ACCESSORIES	CHARACTERISTICS
	RACCORDI	porta tazza e seghe a tazza (tipo TA/AV fino a 3" e tipo TAD da 4" a 6") disponibili di serie, in funzione del modello, nei seguenti diametri: 1" (22 mm) - 1,1/4"(30 mm) - 1,1/2"(37 mm) 2"(48 mm) - 2,1/2"(64 mm) - 3"(73 mm) 4"(98 mm) - 5"(121 mm) - 6"(140 mm)	CONNECTOR	hole saw and hole saw carrier connector (TA/AV type up to 3" and TAD type from 4" to 6") available in the following diameter: 1" (22 mm) - 1,1/4"(30 mm) - 1,1/2"(37 mm) 2"(48 mm) - 2,1/2"(64 mm) - 3"(73 mm) 4"(98 mm) - 5"(121 mm) - 6"(140 mm)
1	PROLUNGA	da 150 mm maschio/femmina	EXTENSION	male/female 150 mm
1	PROLUNGA	da 200 mm maschio/femmina	EXTENSION	male/female 200 mm
1	PUNTA	di centraggio	PILOT	drill
1	MANDRINO	esagonale	MANDREL	hexagonal
2	LEVE	montaggio/smontaggio prolunghe	LEVERS	to assemble/disassemble extensions
1	PISTONCINO	scarica pressione	PISTON	to reduce pressure
1	CHIAVE	a cricco	SPANNER	ratchet
1	CHIAVE	esagonale	SPANNER	hexagonal
1	CACCIAVITE	a taglio	SCREWDRIVER	single cut
2	CHIAVE	a settore	SPANNER	wrench
1	LIBRETTO	uso, manutanzione e conformità	HANDBOOK	operation, maintenance and compliance